



Absolute Versatility In A Powered Speaker

APS-30U / APS-30I

- High output, built –in 30W amplifier
- Portable-Lightweight and easy to set up
- Line/Mic inputs with individual volume controls
- Battery powered for maximum flexibility
- Tone control for smooth response
- Individual level controls for two wireless microphones
- High efficiency design with 6.5” driver
- Aux out/ext speaker jack



APS-30U

(with Built-in UHF Receiver)

- User-selectable 16 UHF channels
- Built-in RF antenna



APS-30I

(with Built-in IR Receiver)

- Dual channel IR receiver
- Built-in IR sensor to eliminate the need of an external sensor

APS-30U



IRH-15c



IRN-10



Specifications*

	APS-30U	APS-30I
Speaker Output Power	30W / 4Ω	
Speaker Type	Magnetic 16.5 cm size	
Wireless Frequency	UHF 16ch, 566.25MHz to 589.75MHz	Ch-1 : 2.06Mz, Ch-2 : 2.56MHz
Channel Number	16 Channel	2 Channel
Frequency Response	50 - 15000Hz	
Tone Control	Bass, Treble	
Mic. Input	φ 6.3 jack	
Line Input	φ 6.3 jack	
Line Output	φ 6.3 jack	N/A
Ext. Speaker Out	φ 6.3 jack	N/A
Power Requirement	AC 100-240V/12V Battery	
Dimensions	220W x 313H x 215D mm	
	8.7W x 12.3H x 8.5D inches	
Weight	4.85kg	

APS-30I

APS-30(U)	Frequency
Ch 1	566.25 MHz
Ch 2	566.75 MHz
Ch 3	568.75 MHz
Ch 4	569.75 MHz
Ch 5	573.05 MHz
Ch 6	574.25 MHz
Ch 7	575.75 MHz
Ch 8	577.50 MHz
Ch 9	578.50 MHz
Ch 10	580.25 MHz
Ch 11	581.75 MHz
Ch 12	582.50 MHz
Ch 13	586.25 MHz
Ch 14	587.25 MHz
Ch 15	589.25 MHz
Ch 16	589.75 MHz

* Due to constant improvements, specifications are subject to change without notice.

AZDEN corporation

P.O. Box 10, Franklin Square, NY 11010, (516)328-7500, FAX (516)328-7506
 e-mail: sales@azdencorp.com, web site: www.azdencorp.com

